

Material Safety Data Sheet

EMERGENCY PHONE NUMBER: (816) 847-6905

SECTION I - IDENTITY

COMMON NAME: 24 fl. oz. PX Fabric Softener, UPC 635672-242009, Item No CS2434FS-Case12

CHEMICAL FAMILY: Laundry Aide

SYNONYMS: Not Applicable

SECTION II - HAZARDOUS INGREDIENTS

PRINCIPLE HAZARDOUS COMPONENTS	%	THRESHOLD LIMIT VALUE
--------------------------------	---	-----------------------

None

SARA requires submission of annual report of release of toxic chemicals that appear in 40 CFR 372. This information must be included in all MSDS's that are copied and distributed for this material.

SECTION III - PHYSICAL & CHEMICAL CHARACTERISTICS

BOILING POINT: 212° F. SPECIFIC GRAVITY (H₂O=1): 0.995

VAPOR PRESSURE (mm Hg): NA VAPOR DENSITY (AIR=1): NA

EVAPORATION RATE (Water=1): 1 pH VALUE @ 25° C (100%): 6.7

SOLUBILITY IN WATER: 100% REACTIVITY IN WATER: Not reactive

APPEARANCE AND ODOR: Opaque blue solution with characteristic odor.

SECTION IV - FIRE FIGHTING MEASURES

FLASH POINT (TCC): > 212° F. (TCC) LEL: Not determined UEL: Not Determined.

EXTINGUISHING MEDIA: Use water spray, dry chemical, water fog, regular foam or carbon dioxide to extinguish flames. Use water spray to cool fire-exposed containers. Water or foam may cause frothing.

SPECIAL FIRE FIGHTING PROCEDURES: Wear protective clothing and self-contained breathing apparatus with full-face shield. Toxic levels of carbon monoxide, carbon dioxide, and irritating amines may be formed. Heating in air may produce irritating amines.

SECTION V - PHYSICAL HAZARDS

STABILITY: UNSTABLE
 STABLE

CONDITIONS TO AVOID: None known.

INCOMPATIBILITY (MATERIALS TO AVOID): None known

**PX FABRIC SOFTENER, UPC 635672-242009,
Quick Identifier**

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, and irritating amines.

HAZARDOUS MAY OCCUR CONDITIONS TO AVOID: Extremes in
POLYMERIZATION X WILL NOT OCCUR
temperature

SECTION VI - HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: EYE: X, INHALATION: , SKIN: , INGESTION: X

SIGNES OR SYPTOMS OF EXPOSURE:

1 ACUTE OVEREXPOSURE:

Eyes: Causes irritation, experienced as pain, with excessive blinking and tear production, and seen as marked excess redness a swelling of the eye with injury to the cornea.

Ingestion: May cause abdominal discomfort, nausea , and diarrhea.

2 CHRONIC OVEREXPOSURE:

Skin: Prolonged contact, as with clothing wetted with material, may cause irritation and discomfort, seen as local redness and swelling

MEDICAL CONDITIONS GENERALLY AGRIVATED BY EXPOSURE:

LIST AS CARCINOGEN NATIONAL Yes I.A.R.C. Yes OSHA Yes
OR POTENTIAL TOXICICOLGY X No MONOGRAPHS X No X NO
CARCINOGEN?

EMERGENCY AND FIRST AID PROCEDURES:

- 1 EYES: Flush eyes with cold water for at least fifteen (15) minutes. Hold eyelids apart while flushing to rinse entire surface of eye and lids with water. Do not attempt to neutralize with chemical agents. Obtain medical attention immediately. Continue flushing for an additional fifteen (15) minutes if medical attention is not immediately available. Do not rub eyes
- 2 SKIN: Wash affected area with plenty of soap and water soap and water. Remove and wash contaminated clothing. Get medical attention if skin irritation develops or persists
- 3 INGESTION: Call a physician or Poison Control Center. Do not induce vomiting. Do give anything by mouth to an unconscious or convulsing person.

SECTION VII- SPECIAL PROTECTION INFORMATION

VENTILLATION:

LOCAL EXHAUST: Not required under normal use. MECHANICAL (General): Acceptable
SPECIAL: None OTHER: None

PROTECTIVE GLOVES: Not required under
normal use

EYE PROTECTION: Not required under
normal use

SECTION VIII - SPECIAL PRECAUTION AND SPILL/LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool dry place. Avoid storage under conditions of temperature.

OTHER PRECAUTIONS: Keep out of the reach of children.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use water spray to dilute and/or wash away to sanitary drain under normal consumer conditions...

WASTE DISPOSAL METHODS: Small (household) quantities may be disposed of via sewer. Disposal is to be performed in accordance with federal, state and local laws.

SECTION IX - DATE AND SIGNATURE

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials in any other process. The stated MSDS is reliable to the best of the company's knowledge and believed accurate as the date indicated. However, no representation, warranty or guarantee of any kind, expressed or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as the suitability and completeness of such information for his own particular use.

CUSTOM SOLUTIONS, INCORPORATED
3330 S. Outer Road E.
Grain Valley, MO. 64029

Revision Date: 1 March 2007
Supersedes: None-New

The submission of this MSDS may be required by law, but this is no assertion that the substance is hazardous when used in accordance with proper safety practices and normal procedures. Data supplied is for use only in connection with occupational safety and health.